

MULTI-FUNCTIONAL COMBINATION LIGHT INSTALLATION GUIDE


Eurolumen
MODEL ELX902

1




CHECK COMPONENTS

2



SWITCH OFF POWER / ALIGN WITH TRACK

3



INSERT ADAPTER INTO TRACK

4



ROTATE / LOCK ADAPTER

5




ADJUST AIMING ANGLE

6



POWER ON / CHECK OPERATION

WIRING DIAGRAM



COMPATIBLE TRACK SYSTEM


POWER SUPPLY

LED

V3: 220V V5: 48V DL: DALI BE: Bluetooth DC: 0-10V NF: ON/OFF

FOLLOW TRACK SYSTEM / DRIVER LABEL

MOUNTING DATA



TRACK-MOUNTED / ADJUSTABLE

TRACK COMPATIBILITY: TBC

PRODUCT SIZE

ADAPTER 190 x 46 mm | ARM 115 mm | HEAD Ø84.5 mm

POWER

30W

CCT / CRI

2700K / 3000K / 3500K / 4000K | CRI 95

BEAM

15° / 20° / 30° / 40° / ADJ. 10-50° / 18-36° / 38-56°

INSTALLATION NOTES

1. Switch off power before installation.

2. Install the adapter into a compatible track and lock securely.

3. Adjust the spotlight to the desired angle.

4. Check operation after installation.

**WARNING**

- Do not install while the power is on.
- Confirm track system voltage compatibility (220V or 48V).
- Ensure the adapter is locked securely before power on.

CERTIFICATIONS / IP RATING: TBC