

LED RECESSED DOWNLIGHT
INSTALLATION GUIDE

Eurolumen

MODEL ELX206

ASYMMETRIC CAPSULE PRISMATIC LENS

1

CHECK COMPONENTS

2

CUT OPENING TO CONFIRMED SIZE

3

CONNECT MATCHED DRIVER

4

ALIGN AND SCREW FIX MESH WINGS

5

PLASTER, SAND AND PAINT FLUSH

6

CHECK FLUSH FIT / POWER ON

WIRING DIAGRAM

ON/OFF: L / N
DALI: DA / DA
0-10V: DIM+ / DIM-
BLUETOOTH: MATCHED DRIVER

FOLLOW THE TERMINAL DIAGRAM ON THE SUPPLIED DRIVER LABEL.

MOUNTING DATA

CUT-OUT	Ø85 mm
CEILING THICKNESS	CONFIRM ON SITE
INSTALLATION TYPE	TRIMLESS / PERFORATED MESH WINGS
PRODUCT SIZE	Ø85 x H85 mm
INPUT	220V AC VIA MATCHED DRIVER
POWER	8W / 12W
LOCATION	INDOOR / DRY LOCATION

Installation must be performed under the guidance of qualified technical personnel.
Switch off and isolate the mains supply before installation or maintenance.
Confirm that the selected driver, dimming control and mounting dimensions match the product label.
Retain this guide with the project handover and maintenance records.

WARNING

- DO NOT INSTALL WHILE POWER IS ON.
- USE ONLY THE MATCHED DRIVER AND CONFIRMED MOUNTING DIMENSIONS.

CE RoHS

INDOOR